# Creating A TCP Shield Account For The Free Plan

If you are wanting to protect your public IP for your MC network from your dedicated system you purchased from OVH for example, but don't need to pay for the bedrock support feature or cannot afford one of the higher plans, you can sign up to TCP Shield using their free plan.

Head over to https://panel.tcpshield.com/register and fill out the details. If you are a Jasmeow.Systems client, please provide the details of the login you just made, we will do the rest.

Click "Add network" and give it an appropriate name:

Add network

On the left hand side, find "Backends" and on the right side, choose "+ Add Set".

Overview

Domains

Backends

+ Add Set

Fill in the relevant details, giving it a name such as "Java" and then putting in the public IP + the port, as shown below, choosing "Save" when done.

Do **NOT** toggle Proxy Protocol if you are running a standard plain vanilla MC or modded forge server. You will only want to toggle this for standalone Paper servers **OR** proxy based configurations such as Velocity or BungeeCord.

Name   Java

Backends   1.1.1.1:25565 ✕

Proxy Protocol

On the left hand side, click "Domains" and in "Step 1", copy the CNAME.

Pop into your DNS such as CloudFlare and update any records you wish to have when joining your MC Network, such as **play, mc, join, @** or any alternative you want to add. You can only add **3** on the free plan, so normally I do play, mc and the @ symbol for the root domain.

In CloudFlare, turn off the cloud so it is just "DNS only". You will have CF reroute sometimes back and fourth causing periodic player connection problems. Not drops, just unreliability in actually joining.

Head back to TCP Shield and click "+ Add Domain" in the bottom right.

Fill in the relevant details, such as the Domain and choose the backend set you made earlier, clicking Add when done.

You can now see it is added and verified. Your final step is to update your MC network configuration.

For Velocity:

Head to the **velocity.toml** and scroll all the way to the bottom, updating the line **haproxy-protocol** to **true**.

For BungeeCord/Waterfall:

Head to **config.yml** and update the line called **proxy_protocol** to **true**.

For standalone Paper:

Have just one server but still want to use TCP Shield? You can still do this by going to:

- For 1.19 servers and above, go to the config folder > paper-global.yml.
- For anything below, find the paper.yml in the root directory.

In this yml file, find the line **proxy-protocol** and set it to **true**.

> Ignore all other lines, it's squished between the two proxy types to add to the confusion! It's not related to either as in YML it's a indentation to the option variable "proxies" but not indented with bungee-cord or velocity.

Revision #1
Created 10 December 2023 03:51:04 by JasmeowTheCat
Updated 1 April 2024 21:39:41 by JasmeowTheCat